

Socket outlet with voltage indication, pin earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, plug-in terminals, yellow

195-66622

4 year warranty

Socket outlet with voltage indication, pin earthing and shutters. This socket outlet has a flush-mounting depth of 28.5 mm and is equipped with a plug-in terminals and claw fixing. Includes finishing set. A faceplate in the colour of your choice must be ordered separately. Finishing colour: yellow.

Wires that remain fixed:

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the flush-mounting box.

Faster and easier installation:

- all connections terminals are located at the top of the base:
 - to ensure all wires can be cut and stripped at the same length
 - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the flush-mounting box without the wiring pushing it back up.


Niko quality:

- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop
- metal base is held firmly in place, even on uneven walls, doesn't break and is not subject to stress cracking (small ruptures)
- firm metal claws with a large engagement depth (31 mm) remain fixed when mounted and can be screwed tightly to ensure that the socket outlets can remain fixed in the wall for a longer time and to avoid the mechanisms should become warped

Technical data

Socket outlet with voltage indication, pin earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, plug-in terminals, yellow.

- Fixing method
 - with claws that can be rotated open using screws with a slotted screw head (slot 0.8 x 5 mm), for mounting in a flush-mounting box with grip surfaces
 - depth of engagement of claws: 31 mm
 - claws turn back completely when loosened
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires
- Stripping length
 - 14 mm stripping length
 - indelibly indicated at the rear side: stripping length
- Fire safety
 - self-extinguishing plastic components (central plate and base cover): complies with a filament test of 650




niko

°C

– halogen-free

- The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE



16 A
250 Vac

Wiring diagram

