

# Finishing set for electrically separated roll-down shutter switch, light grey

102-65905

4 year warranty

Finishing set for an electrically separated roll-down shutter switch. Finishing colour: light grey.

## Technical data

Finishing set for electrically separated roll-down shutter switch, light grey. This central plate is surrounded with a flat edge that is equipped at all 4 corners with a rectangular opening, each containing a multi-positional snap hook. The construction of the central plate ensures that the faceplate can always be attached flat to the wall, even in cases of untidy plasterwork. This works in two directions: If the flush-mounting box sticks out of the plasterwork, the multi-positional snap hooks can compensate for a 1 to 1.2 mm margin; if the flush-mounting box is sunk too deeply in the plasterwork, the snap hooks can compensate for up to a 1.8 mm margin. The flat edge around the central plate also has 4 round openings that ensure the correct positioning of the faceplate in relation to the central plate. After mounting all components (faceplate, finishing set and switch), no metal parts are visible thanks to the flat edge of the central plate.

- Number of control buttons: 4 control buttons
  - Material central plate: The central plate is made of rigid PC and ASA. The base material is coloured in mass.
  - Colour: light grey (coloured in mass, approximately NCS S 1002 - Y, RAL 080 80 05)
  - Print: On the left key, 'stop' is indicated at the top, 'start' at the bottom. On the right key, an arrow pointing upwards is indicated at the top, an arrow pointing downward at the bottom. The two keys and the intermediate plate form one unit.
  - Dismantling: For dismantling the central plate, the flat edge is equipped with two notches indicated by a screwdriver symbol. The central plate can easily be dismantled using a slotted screwdriver.
  - Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
  - Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
  - Fire safety
    - the plastic parts of the central plate are self-extinguishing (comply with a filament test of 650 °C)
    - the plastic parts of the central plate are halogen-free
  - Dimensions of finishing with flat edge: 56 x 56 mm (HxW)
- Dimensions of visible area of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 55.8 x 55.8 x 10.5 mm
  - Certification marks: CEBEC, SEMKO, VDE, DEMKO, NF, KEMA, ÖVE
  - Marking: CE

