

Single faceplate, Niko Pure alu blue grey brushed

220-76100

4 year
warranty

Single faceplate from the range Niko Pure. Niko Pure alu blue grey brushed.

Technical data

Single faceplate, Niko Pure alu blue grey brushed.

- Simple faceplate for one switch.
- Colour: alu blue grey (approximately NCS S 8005 - R80B, RAL 240 30 05)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu blue grey). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 83 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE

