

Threefold faceplate, horizontal 71 mm centre distance, for one 45x45 function, a socket outlet and a double switch function, Niko Toggle alu grey brushed

155-57716

4 year warranty

The Niko Toggle threefold horizontally oriented faceplate clicks onto one 45x45 function a socket outlet and a double switch function that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko 45x45 function, a Niko Rocker and Niko Toggle socket outlet finishing set and a Niko Toggle double switch function. The faceplate combines with any available Niko Rocker and Niko Toggle socket outlet finishing set and a Niko Toggle double switch function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of brushed aluminium. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm. Niko recommends a design combination with a finishing set in the following colour: alu grey.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base
- Designed to fit any available 45 x 45 mm function

Technical data

Threefold faceplate, horizontal 71 mm centre distance, for one 45x45 function, a socket outlet and a double switch function, Niko Toggle alu grey brushed.

- Colour: alu grey (approximately NCS S 2002 - G, RAL 000 80 00)
- Recommended colour central plate: alu grey
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of brushed aluminium.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance

of IK06

- Dimensions (HxWxD): 83 x 225 x 13 mm
- Dimensions visible (HxWxD): 83 x 225 mm
- Marking: CE

