

Presence or absence detector 360°, 2 channels, 16 m, KNX®, flush-mounting, square

351-25033

4 year warranty

The presence or absence detector with two channels and daylight control for surface mounting is suitable for switching the indoor lighting on and off. The detector is equipped with an integrated light sensor and is only compatible with KNX®. Finishing colour: white







- Combination of master/secondary possible
- Can be placed at a height of up to 6 metres

Presence detector for use in standard rooms such as offices, meeting rooms, etc.

- Everything can be programmed using ETS software
- Very simple programming
- Can be programmed as a presence or absence detector
- 2 channels for heliometer setting with standby lighting
 - 1 channel for turning the lighting on and off
 - 1 channel for turning the HVAC installation on and off

Detection range



D			
2 m	4 m	5 m	10 m
2.5 m	5 m	6 m	12 m
3 m	6 m	7 m	14 m
3.5 m	7 m	8 m	16 m
4 m	8 m	8 m	16 m
5 m	8 m	8 m	16 m
6 m	8 m	8 m	16 m

Technical data

Article number	351-25033
Input voltage	24 Vdc \pm 10 %
Detector output	24 V (ON/OFF)
Light intensity range	5 lux – 2000 lux
Number of channels	2 channels
Detection angle	360°
Detection range (PIR)	ø 14 m from a height of 3 m
Ambient temperature	-20 – +40 °C
Mounting method	flush-mounting
Mounting height	2 – 6 m
Dimensions visible (HxWxD)	35 mm
Dimensions (HxWxD)	88 x 88 x 50 mm
Protection degree	IP20
Marking	CE

Dimensions

