

# Double socket outlet with side earthing and shutters, vertical, cream

100-67865

4 year  
warranty

## Technical data

Double socket outlet with side earthing and shutters, vertical, cream

- Type of earthing: side earthing
- Power: 16 A/230 Vac
- Flush-mounting frame
  - 1 mm-thick metal
  - galvanized on all sides
  - with 2 grooves
- Material faceplate: The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is mass-dyed.
- Material earthing: side earthing in high quality brass
- Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Wire connection
  - contact buses fitted with plug-in terminals for clamping the wires
- Earthing wire capacity
  - 2 x 2,5 mm<sup>2</sup> + 2 x 4 mm<sup>2</sup> wire in the earthing terminal
- – All plastic components are self-extinguishing (comply with a filament test of 650°C) and are halogen-free.
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Dimensions (HxWxD): 106.8 x 80 x 63 mm
- Certification marks: KEMA, DEMKO, VDE
- Marking: CE



$\frac{16 \text{ A}}{250 \text{ Vac}}$



**niko**

100-67865 - 31 - 10-2024

## Wiring diagram

