

Twofold faceplate, 60 mm centre distance, for 2 socket outlets, Niko Rocker and Niko Toggle, alu black brushed

224-74201

4 year warranty

The twofold faceplate clicks onto two socket outlet functions that have been installed with a centre distance of 60 mm. The faceplate combines with any available Niko Rocker and Niko Toggle socket outlet finishing set.

It consists of an upper frame and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu black). The anodisation process may result in slight colour differences. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated. The upper frame is 6 mm thick and the lower frame 2 mm.


Niko recommends a design combination with the finishing set in the following colour: Niko recommends a design combination with a black coated central plate (colour code 161).

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Designed to fit the standard socket outlet base

Technical data

Twofold faceplate, 60 mm centre distance, for 2 socket outlets, Niko Rocker and Niko Toggle, alu black brushed.

- Double faceplate for two switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: Niko recommends a design combination with a black coated central plate (colour code 161).
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu black). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Varnish lower frame: The lower frame is enamelled black.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D



niko

- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 10 mm
- Dimensions visible (HxWxD): 143 x 83 x 8 mm
- Marking: CE

