

Threefold faceplate, vertical 71 mm centre distance, for a single and two double switch functions, Niko Toggle steel white coated

154-57953

4 year warranty

The Niko Toggle threefold vertically oriented faceplate clicks onto a single and two double switch functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.

Niko recommends a design combination with a finishing set in the following colour: steel white coated.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)



Technical data

Threefold faceplate, vertical 71 mm centre distance, for a single and two double switch functions, Niko Toggle steel white coated.

- Colour: enamelled steel white (approximately NCS S 1002 - B50G, RAL 000 90 00)
- Recommended colour central plate: steel white coated
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Varnish upper frame: The upper frame is enamelled white.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Lighting element
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 x 83 x 13 mm
- Dimensions visible (HxWxD): 225 x 83 mm

niko

• Marking: CE



www.niko.eu

niko

154-57953 - 23.01.-2025