

Twofold faceplate with 71 mm centre distance, Niko Intense sterling coated

121-76800

4 year
warranty

Twofold faceplate with 71 mm centre distance from the range Niko Intense. Niko Intense sterling coated

Technical data

Twofold faceplate with 71 mm centre distance, Niko Intense sterling coated.

- Double faceplate for two switches.
- Colour: enamelled sterling (approximately NCS S 4000 - N, RAL 9007)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made from impact-resistant, dimensionally stable polycarbonate.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Varnish upper frame: The upper frame is enamelled sterling.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 85 x 154 x 8.9 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

