

# Threefold faceplate, horizontal 71 mm centre distance, for a socket outlet, a double and a single switch function, Niko Rocker alu grey brushed

155-56717

4 year warranty

The Niko Rocker threefold horizontally oriented faceplate clicks onto a socket outlet, a double and a single switch function that have been horizontally installed next to each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker and Niko Toggle socket outlet finishing set and Niko Rocker for single and double switch functions. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of brushed aluminium. The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA). The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu grey for Niko Rocker and Niko Toggle finishing sets and anthracite coated for other finishing sets.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base

## Technical data

Threefold faceplate, horizontal 71 mm centre distance, for a socket outlet, a double and a single switch function, Niko Rocker alu grey brushed.

- Colour: alu grey (approximately NCS S 2002 - G, RAL 000 80 00)
- Recommended colour central plate: alu grey for Niko Rocker and Niko Toggle finishing sets and anthracite coated for other finishing sets
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of brushed aluminium.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 13 mm
- Dimensions visible (HxWxD): 83 x 225 mm
- Certification marks: CEBEC, NF
- Marking: CE

**niko**

155-56717 - 05-04-2025

CE

[www.niko.eu](http://www.niko.eu)

***niko***

155.56717 - 05-04-2025