

Modular external audio unit for flush-mounting 3 modules: audio, display and code lock

Function description

This modular flush-mounted external unit offers an elegant and flexible solution for your projects (up to 256 housing units). The start screen of the display can be configured individually. The front plate is made from high-quality brushed stainless steel. The modular external audio unit is equipped with an integrated twilight switch and an audio, display and code lock module.

It makes it possible to activate a door call, have a conversation and open the door. Thanks to the 3 function keys on the display module, you can easily navigate through the alphabetically sorted resident list. You can also use the code lock module to navigate via the flat number. Visual feedback for the visitor (colour pictographs) is also provided.



Technical data

Reference number	10-286
Dimensions	440 x 200 x 3 mm (HxWxD) (front plate) 420 x 180 x 50 mm (HxWxD) (flush-mounting frame)
Finishing colour, material	brushed steel; modules made of black aluminium
Vandal proof	yes
Input current in standby	I(a) = 0.4 mA, I(P) = 140 mA
Max. input current	I(Pmax) = 245mA
Display	160 x 104 pixels (fully graphic, monochrome)
Wiring	3-wired
Extra terminals	yes (e.g. for connecting door opener)
Protection degree	IP44
Ambient temperature	-20 °C to +50 °C
Marking	CE marking
Max. number of housing units	256
Conversation mode	hands-free conversation (standard), full duplex conversation possible
Direct dialling	possible (in combination with 10-850)
Error detection and indication	yes
Memory	removable EEPROM memory
Configuration	Niko Configuration Software for access control

Dimensions

