

# Threefold faceplate, 60 mm centre distance, vertical, Niko Intense matt black coated

130-76300

4 year  
warranty

Threefold faceplate with 60 mm centre-to-centre distance, vertical, from the range Niko Intense. Niko Intense matt black coated

## Technical data

Threefold faceplate, 60 mm centre distance, vertical, Niko Intense matt black coated.

- Threefold faceplate for three switches.
- Colour: enamelled matt black (approximately NCS S 9000 N, RAL 9005)
- Recommended colour central plate: Niko recommends a design combination with a black coated central plate (colour code 161).
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made from impact-resistant, dimensionally stable polycarbonate.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Varnish upper frame: The upper frame is enamelled matt black.
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 203 x 85 x 8.9 mm
- Certification marks: CEBEC, NF, ÖVE, KEMA
- Marking: CE

