

Niko dimmer switch for Hue system, Niko Intense anthracite coated

133-91004

4 year warranty

With this wireless and battery-free dimmer switch, you can operate the Philips Hue lamps effortlessly. Determine in the Philips Hue app what each button must do (switching on and off, dimming, activating scene settings). Mechanism including push button and faceplate anthracite coated. Philips Hue Bridge v2 required and not included.

Technical data

Niko dimmer switch for Hue system, Niko Intense anthracite coated.

- Function: The dimmer switch consists of a base, a double key and a single faceplate.
- Communication protocol: Zigbee® Green Power
- Maximum radio frequency power: 7 dBm
- Operating frequency: 2.4 GHz
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Marking: CE

Base for the Niko dimmer switch for Hue System.


- Number of control buttons: 4 control buttons

- Fixing method
screw fixing or gluing
- Marking: CE

Double key, for wireless dimmer switch (Hue®, Bluetooth®, EnOcean®, KNX®), anthracite coated.

- Number of control buttons: 4 control buttons
- Material central plate: The central plate is enamelled and made of rigid PC and ASA.
- Colour: enamelled anthracite (approximately NCS S 7502 - R, RAL 7022)
- Dismantling: To dismount simply pull the central plate off the mechanism.
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Fire safety
 - the plastic parts of the central plate are self-extinguishing (comply with a filament test of 650 °C)
 - the plastic parts of the central plate are halogen-free
- Dimensions of finishing: 45 x 45 mm (HxW)
- Dimensions (HxWxD): 44.5 x 44.5 x 8.6 mm
- Marking: CE

Single faceplate, Niko Intense anthracite coated.



niko

- Simple faceplate for one switch.
- Colour: enamelled anthracite (approximately NCS S 7502 - R, RAL 7022)
- Frame composition: It is made of dimensionally stable pc+asa.
- Varnish upper frame: The upper frame is enamelled anthracite.
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Certification marks: CEBEC, SEMKO, VDE, NF, ÖVE, KEMA
- Marking: CE

