

External video unit for Niko Home Control, with 1 illuminated touch button

550-22011

4 year warranty

This ultra-flat external video unit for flush mounting is finished with a black front plate made of anodised aluminium (3 mm thick). The device is equipped with a 120° HD colour camera and a Plexiglass name plate that can be engraved. The touch button requires no maintenance and is extremely durable. The external video unit is supplied with a flush-mounting box. This external unit has 1 illuminated touch button. This unique lighting concept (patent pending) provides refined and homogeneous illumination of the engraved nameplate, guaranteeing good visibility in the dark. Combined with touchscreen 3 (or a smartphone or tablet) as an internal video unit, access control can be integrated into a Niko Home Control installation via the external video unit.

If you want to receive incoming calls via the Niko Home app on a tablet, contact your tablet vendor to ensure that your tablet meets the following minimum requirements:

- It has speakers and a microphone
- It supports telephony
- In case of an Android device, it operates on version 9 or higher

Please note: we recommend providing at least one touchscreen 3 on top of the smartphones and/or tablets, because a wired device is always more reliable than a mobile one.

- The HDR camera offers crisp and sharp imaging in high-contrast situations

Technical data

External video unit for Niko Home Control, with 1 illuminated touch button.


- Compatible with the Niko PoE+ power supply (550-00502) or a PoE+ power source (Mode A – pins 1, 2+; 3, 6-)
- Acknowledgement tone when pressing the bell button
- Material push buttons: metal with gilded, maintenance-free contacts
- Long-life energy-saving name plate lighting
- 5 mm thick, indestructible and vandal proof name place in Plexiglass
- Mounting method: flush-mounting
- Dimensions front plate: 256 x 110 x 3 mm (HxWxD)
- Dimensions flush-mounting box: 239 x 89 x 47 mm (HxWxD)
 - 8 MP HD colour camera
 - Light sensitivity camera: 1 lux
 - Camera angle: 120°
- Wiring technique: IP wiring
- Thickness of front plate: 3 mm aluminium
- Finishing colour: black
- Protection degree: IP53
- Marking: CE



niko



Dimensions



Wiring diagram

