

# Flush-mounting external unit with 18 bells and colour camera

10-318

4 year warranty

This ultra-flat flush-mounting unit is finished with 3 mm-thick aluminium. It is equipped with a colour camera. The external unit is equipped with a 5 mm-thick name plate in Plexiglas which is vandal proof. The metal-plated push-button contacts are maintenance-free and durable. The external unit includes the flush-mounting box. This external unit has 18 bells.

## Technical data

Flush-mounting external unit with 18 bells and colour camera.

- Function:
  - each non-programmed push button can operate the light, light symbol supplied
- Acknowledgement tone when pressing the bell button
- material push buttons: metal with gilded, maintenance-free contacts
- long-life energy-saving name plate lighting
- 5 mm thick, indestructible and vandal proof name place in Plexiglass
- internal memory for the exchange of data between identical external units (EEPROM)
- Fixing method
  - win:clip principle
- Dimensions front plate: 296 x 398 x 3 mm (HxWxD)
- Dimensions flush-mounting box: 247 x 374 x 40 mm (HxWxD)
- Dimensions name field: 19 x 62 mm (HxW)
- Microphone: volume and microphone sensitivity can be adjusted manually
  - Features of colour camera:
    - type: CMOS sensor
    - resolution: 380 horizontal TV lines
    - focal length: 2.0 mm (F=2.5)
    - light sensitivity: 0 lux with IR, 1 lux without IR
    - video output: 1 Vpp, symmetrical
    - diagonal coverage angle: 130°.
- Wiring technique: 6-wire technology required
- Extra terminal
  - extra terminal for the local control of a 24 V DC contact.
  - adjustable time settings such as the door opener time, the activation time and the conversation time.
- Input current at rest:  $I(a) = 1.2 \text{ mA}$ ,  $I(P) = 173 \text{ mA}$  in standby
- Maximum input current:  $I(P_{\max}) = 178 \text{ mA}$
- Thickness of front plate: 3 mm aluminium
- Finishing colour: grey
- Dimensions (HxWxD): 296 x 398 mm
- Marking: CE



CE

[www.niko.eu](http://www.niko.eu)

**niko**

10-318 - 08-01-2024