

Tender text Article number 353-601021

Presence detector P41MR, 230 V, secondary, 12-13 m, for flush mounting (SnapFit), white



Proposed functionalities description according to BIPS 4.7.9

Presence detector P41MR, 230 V, secondary, 12-13 m, for flush mounting (SnapFit), white

SPECIFICATIONS

| | |
|-----------------------|-----------------------------|
| Configuration | secondary |
| Detector technology | PIR |
| Mounting method | flush-mounting (SnapFit) |
| Input voltage | 230 Vac ± 10 %, 50 Hz |
| Detector output | 230 V (ON/OFF) |
| Detection angle | 360° |
| Detection range (PIR) | ø 12 m from a height of 3 m |
| Ambient temperature | -25 – +40 °C |
| Flush mounting depth | 56.9 mm |
| Drill diameter | 76.0 mm |
| Mounting height | 2 – 3.5 m |
| Marking | CE |
| Protection degree | IP20 |

Proposed functionalities description according to BIPS 4.7.10

Mounting method

The detector is suitable for mounting in all types of ceilings without the use of additional elements (e.g. tiles) to guarantee stable mounting. The detector can easily be removed without damaging the ceiling or ceiling tiles.

Configuration app

All detectors in the installation can be configured using the app and 2-way Bluetooth® communication between a smartphone or tablet and the detector. No additional configuration tools are required. The settings can be stored as a template for other detectors. The firmware of the detector can be updated via the app.

PIN code

The detector can be protected with a 4-digit PIN code in the app to prevent others from controlling the detector or modifying its settings.

**Event log**

The event log in the app shows all the changes you made to the settings of a specific detector.

Sensitivity

The detector's sensitivity for detecting movement can be set using the app. The 360° detection range can be divided into three sectors each covering 120°. The sensitivity of these sectors can be set separately in 4 levels and a sector can be switched off completely.

Documentation

Documentation is available in digital format on an online portal. This portal also allows to store, review and share settings in PDF and/or Excel format. The detectors can be organised into specific projects or groups. Existing detector settings can be used as a template for new detectors.

Detection range

The detection range is documented in accordance with EN/IEC 63180.