

Motion detector, 230 V, Zigbee®, 5 m, 110°, wireless, for surface mounting, white

552-80401

4 year warranty

The wireless motion detector can be used to control other switching contacts. For example, when motion is detected, you can control the contact of another connectable switch, dimmer or motor control.

Since the motion detector is powered by a button battery and is supplied with a self-adhesive mounting plate, it can be easily attached anywhere.


This motion detector can be used in combination with the wireless smart hub for Niko Home Control (552-00001) or with the wireless bridge for Niko Home Control (550-00640) for use in a bus wiring installation. This makes it possible to configure additional functionalities with the Niko Home Control programming software.

Finishing colour: white

Compatible secondary detectors: 552-80401



Detection range



230 V



master/
secondary



110°



ø 5 m from
a height of
2.5 m



2.5 – 2.8 m



surface
mounting

niko

Technical data

Article number	552-80401
Compatible secondary detectors	552-80401
Input voltage	battery CR2450
Detection angle	110°
Detection range (PIR)	ø 5 m from a height of 2.5 m
Ambient temperature	0 – 40 °C
Mounting method	surface mounting
Mounting height	2.5 – 2.8 m
Dimensions (HxWxD)	51 x 51 x 34 mm
Operating frequency	2.4 GHz
Maximum radio frequency power	7 dBm
Protection degree	IP20
Modification of settings	Niko Home Control programming software
Marking	CE

Dimensions

