

Twofold faceplate with 71 mm centre distance, Niko Pure liquid black

242-76800

4 year
warranty

Twofold faceplate with 71 mm centre distance from the range Niko Pure. Niko Pure liquid black

Technical data

Twofold faceplate with 71 mm centre distance, Niko Pure liquid black.

- Double faceplate for two switches.
- Colour: enamelled liquid black (approximately NCS S 9000 N, RAL 9005)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of hard-coated PMMA.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - completely self-extinguishing faceplate
 - complies with a filament test of 650 °C
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE

