

Splashproof double horizontal wall socket with pin earthing, shutters and plug-in terminals; includes surface-mounting box with two inputs on the upper side, white

701-37754

4 year warranty

With this horizontal combination, the two splashproof surface-mounting wall sockets are equipped with pin earthing, shutters and plug-in terminals. Both wall sockets are also equipped with a hinged protective cover and are pre-wired (2.5 mm²) and mounted in a double splashproof surface-mounting box with two inputs on the upper side. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. Colour combination: white.

Wires that remain fixed:

- wire is fixed firmly due to the high-quality plug-in terminal with a long life span, tested according to the norm
- since the conductor release on the mechanisms is located at the front, the wiring cannot push on the release when you place it in the box

Faster and easier installation:

- all connections terminals are located at the top of the base:
 - to ensure all wires can be cut and stripped at the same length
 - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the box without the wiring pushing it back up.

Niko quality:

- long life span since the plug-in terminal stays within the limits of the norm during a temperature and power drop

Technical data

Splashproof double horizontal wall socket with pin earthing, shutters and plug-in terminals; includes surface-mounting box with two inputs on the upper side, white.

- Number of mechanisms: 2
- Cable space
 - 15.7 mm wiring space under the mechanism
 - mechanism is held by 2 laterally positioned holders in the box
 - a snap connector holds the wired mechanism in place
- Wire connection
 - contact buses fitted with plug-in terminals for clamping the wires
 - manual release or release with a screwdriver from the front side
- Wire capacity
 - all connection terminals at the top side of the base
 - up to 2 x 2.5 mm² wire per terminal
- Stripping length
 - 12 mm stripping length
 - indelibly indicated at the rear side: stripping length and wiring diagram
 - indelibly indicated at the front side: terminals and switch symbol
- Chemical resistance: tested and approved for use in environments with ammonia levels up to 20 ppm



niko

- Protection degree: IP55 for the combination of a socket outlet and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: white (coloured in mass, approximately NCS S 0502 - Y50R, RAL 9010)
- Certification marks: CEBEC, NF
- Marking: CE

$\frac{h_V}{2}$ 16 A
250 Vac

