

# Single faceplate, Niko Pure alu black brushed

158-76100

4 year  
warranty

Single faceplate from the range Niko Pure. Niko Pure alu black brushed.

## Technical data

Single faceplate, Niko Pure alu black brushed.

- Simple faceplate for one switch.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu black). The anodisation process may result in slight colour differences.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 83 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

