

Twofold faceplate, vertical 60 mm centre distance, for a double and a single switch function, Niko Toggle alu black brushed

224-57254

4 year warranty

The Niko Toggle twofold vertically oriented faceplate clicks onto a double and a single switch function that have been vertically installed on top of each other with a centre distance of 60 mm. The faceplate combines with any available Niko Toggle single and double switch function. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu black). The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated. The upper frame is 6 mm thick and the lower frame 2 mm. Niko recommends a design combination with a finishing set in the following colour: alu black.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)

Technical data

Twofold faceplate, vertical 60 mm centre distance, for a double and a single switch function, Niko Toggle alu black brushed.

- Double faceplate for two switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu black
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu black).
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Varnish lower frame: The lower frame is enamelled black.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 60 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C



niko

- halogen-free
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 143 x 83 x 13 mm
- Dimensions visible (HxWxD): 143 x 83 mm
- Marking: CE

