


# Threefold faceplate, horizontal 71 mm centre distance, for a single switch and two socket outlet functions, Niko Rocker alu blue grey brushed

226-56709

4 year warranty

The Niko Rocker threefold horizontally oriented faceplate clicks onto a single switch and two socket outlet functions that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Rocker switch function and Niko Rocker and Niko Toggle socket outlet finishing set. The faceplate combines with any available Niko Rocker single switch function and a Niko Rocker and Niko Toggle socket outlet finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu blue grey). The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), blue grey coated. The upper frame is 6 mm thick and the lower frame 2 mm.

Niko recommends a design combination with a finishing set in the following colour: alu blue grey.



- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base

## Technical data

Threefold faceplate, horizontal 71 mm centre distance, for a single switch and two socket outlet functions, Niko Rocker alu blue grey brushed.

- Threefold faceplate for three switches.
- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu blue grey
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu blue grey).
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), blue grey coated
- Varnish lower frame: The lower frame is enamelled blue grey.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Lighting element
  - the faceplate is fitted with a light guide
  - the light guide is made of a translucent plastic
  - the light guide transports the light from the optional LED to the lever
  - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Centre-to-centre distance: 71 mm

**niko**

- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP21 D
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 13 mm
- Dimensions visible (HxWxD): 83 x 225 mm
- Certification marks: CEBEC, NF
- Marking: CE

