

Fivefold faceplate, 71 mm centre distance, Niko Pure steel champagne coated

166-76005

4 year
warranty

Fivefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure. Niko Pure steel champagne coated

Technical data

Fivefold faceplate, 71 mm centre distance, Niko Pure steel champagne coated.



- Fivefold faceplate for five switches.
- Colour: enamelled champagne (approximately NCS S 4005 - Y20R, RAL 080 70 10)
- Recommended colour central plate: steel champagne coated
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), champagne coated.
- Varnish upper frame: The upper frame is enamelled champagne.
- Varnish lower frame: The lower frame is enamelled champagne.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 367 x 8.9 mm
- Dimensions visible (HxWxD): 83 x 367 x 8 mm
- Certification marks: CE, SEMKO, VDE, NF, KEMA, ÖVE
- Marking: CE

