

# Threefold faceplate, 71 mm centre distance, Niko Pure steel champagne coated

157-76700

4 year warranty

Threefold faceplate with 71 mm centre-to-centre distance from the range Niko Pure. Niko Pure steel champagne coated

## Technical data

Threefold faceplate, 71 mm centre distance, Niko Pure steel champagne coated.

- Threefold faceplate for three switches.
- Colour: enamelled steel champagne (approximately NCS S 4005 - Y20R, RAL 080 70 10)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of steel.
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA).
- Varnish upperframe: The upperframe is enamelled champagne.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Centre-to-centre distance: 71 mm
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 8.9 mm
- Dimensions visible (HxWxD): 83 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE



CE

[www.niko.eu](http://www.niko.eu)

**niko**

157-76700 - 22.06.2024