

# Motion detector, Niko Home Control, 16 m, 180°, IP54, with orientable lens, for surface mounting, white


550-20200

4 year warranty

This motion detector is suitable for outdoor use, for example, along the driveway, on the terrace or in the garden. It is also equipped with a built-in light sensor. You aim the motion detector wherever you wish and partition the detection area using a cover mask. The Niko Home Control system supplies power to the device.  
Finishing colour: white  
Compatible secondary detectors: 550-20200



### Detection range



H	A Across	B Towards
2 m	11 m	5.5 m
2.5 m	14 m	7 m
3 m	16 m	8 m

Niko Home Control

master/  
secondary

180°

16 m from  
a height of  
3 m

2 – 3 m

surface  
mounting

**niko**

## Technical data

Article number	550-20200
Compatible secondary detectors	550-20200
Input voltage	26 Vdc (SELV, safety extra-low voltage)
Detector output	26 V
Light intensity range	5 lux – ∞
Switch-off delay	8 s – 30 min
Detection angle	180°
Detection range (PIR)	16 m from a height of 3 m
Ambient temperature	-20 – +45 °C
Mounting method	surface mounting
Mounting height	2 – 3 m
Dimensions visible (HxWxD)	70 x 90 x 130 mm
Dimensions (HxWxD)	70 x 90 x 130 mm
Protection degree	IP54
Marking	CE

## Accessories

390-20050      Mounting brace for outdoor motion detector, white

## Dimensions

