

# Socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, screw terminals, orange

198-66600


4 year warranty



Socket outlet with pin earthing and shutters. This socket outlet has a flush-mounting depth of 28.5 mm and is equipped with screw terminals and claw fixing. Includes finishing set. A faceplate in the colour of your choice must be ordered separately. Finishing colour: orange.

## Technical data

Socket outlet with pin earthing and shutters, flush-mounting depth 28.5 mm, base and finishing set, screw terminals, orange.

- Colour: The cover of the socket outlet and the central plate are coloured in mass, orange (approximately RAL 2008) and ensures that after the removal of the central plate, the socket outlet function remains clearly indicated. This is applicable in places where there are many circuits with specifically defined functions, for example, emergency power supplies in hospitals. The central plate is made of rigid PC
- Fixing method
  - with claws that can be rotated open using screws with a slotted screw head (slot 0.8 x 5 mm), for mounting in a flush-mounting box with grip surfaces
  - depth of engagement of claws: 31 mm
  - claws turn back completely when loosened
- End border: 4 rectangular openings (7 x 2.5 mm) which, if the flush-mounting box protrudes from the plasterwork, can compensate for a margin of between 1 and 1.2 mm, so that the faceplate can still butt up perfectly against the wall
- Wire connection
  - the sockets are fitted with cage clamps with permanent screws with combination screwheads (Pz2 or slot 1 x 5.5 mm)
  - every screw is provided with a screwdriver slot that prevents the screwdriver from sliding off the screwhead.
- Stripping length
  - 14 mm stripping length
  - indelibly indicated at the rear side: stripping length
- Fire safety
  - self-extinguishing plastic components (central plate and base cover): complies with a filament test of 650 °C
  - halogen-free
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP21D
- The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE



 16 A  
250 Vac 

### Wiring diagram

