

Presence detector, KNX®, 2 channels, 14 m, for flush-mounting box, white

25032

4 year warranty

Master-secondary presence detector for universal use thanks to versatile accessories. daylight control for 2 zones, 1 secondary zone (ON/OFF), HVAC, brightness threshold and switch-off delay adjustable during operation, orientation light, full and semi-automatic mode.

Finishing colour: white

Compatible secondary detectors: /



- Ideal for KNX applications in industrial buildings, offices, classrooms, meeting rooms, etc.
- 2 light channels for daylight control of 2 light zones or 1 light channel for light switching
- 1 HVAC channel
- Master-secondary mode
- Full or semi-automatic operation and various dimming functions
- Up to 8 light scenes can be programmed
- Dynamic value adjustment for switch-off delay and brightness or lux level (from Firmware V2.7)
- orientation light after movement or active when insufficient daylight available (from Firmware V2.7)
- Automatic switch-off threshold (from Firmware V2.7)
- Other colours on request



KNX®



master/
secondary



360°



ø 14 m from
a height of
3 m



2 – 6 m



flush-
mounting
box

niko

25032 - 30-08-2024

Technical data

Article number	25032
Compatible secondary detectors	/
Input voltage	30 Vdc via KNX®-bus
Detector output	KNX®
Maximum power consumption	0.3 W
Maximum current consumption	10 mA
Light intensity range	10 lux – 2000 lux
Number of channels	2 channels
Switch-off delay	1 s – 24 min
Detection angle	360°
Detection range (PIR)	ø 14 m from a height of 3 m
Ambient temperature	-20 – +40 °C
Mounting method	flush-mounting box
Mounting height	2 – 6 m
Dimensions visible (HxWxD)	105 x 105 x 35 mm
Dimensions (HxWxD)	105 x 105 x 50 mm
Protection degree	IP20
Impact resistance	IK02
Modification of settings	ETS software
Marking	CE

Accessories

351-25330	Cover plate, white
351-25420	Surface-mounting box, white