

Splashproof signalling device with transparent lens and LEDs (LED colour: white), white

700-38200

4 year
warranty

This surface-mounting signalling device is equipped with a transparent cover and LEDs (LED colour: white). It is designed to be mounted in a splashproof mounting box. This device is extremely well-suited for use in damp areas and in demanding environments. Colour: transparent white

Faster and easier installation:

- all connections terminals are located at the top of the base:
 - to ensure all wires can be cut and stripped at the same length
 - to guarantee more space under the mechanism, so you can easily fold the wires and place the mechanism in the box without the wiring pushing it back up.

Technical data

Splashproof signalling device with transparent lens and LEDs (LED colour: white), white.

- Colour: The base material is coloured light grey in mass (approximately NCS S 1502 - B, RAL 7035)
- Sealing: The cover has an integral closure and is hermetically sealed onto the appropriate box.
- LED colour: white
- Number of mechanisms: 1
- Surface-mounting box: The function is designed to be mounted in a splashproof mounting box. The function has an integral closure and is hermetically sealed onto the appropriate box (to be ordered separately).
- Chemical resistance: ammonia-rich environments may cause faster ageing of the base
- Ambient temperature: -25 – +55 °C
- Protection degree: IP55 for the combination of a function and a splashproof mounting box
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Certification marks: CEBEC
- Marking: CE



250 Vac

