

# Threefold faceplate, vertical 71 mm centre distance, for a double switch, a socket outlet and a 45x45 function, Niko Toggle alu black brushed

224-57960

4 year warranty

The Niko Toggle threefold vertically oriented faceplate clicks onto a double switch, a socket outlet and a single switch function that have been vertically installed on top of each other with a centre distance of 71 mm. The faceplate combines with any available Niko Toggle for double switch function, Niko Rocker and Niko Toggle socket outlet finishing set and Niko 45 x 45 mm finishing set. It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of anodised brushed aluminium (alu black). The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated. The upper frame is 6 mm thick and the lower frame 2 mm.


Niko recommends a design combination with a finishing set in the following colour: alu black.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)
- Designed to fit the standard socket outlet base
- Designed to fit any available 45 x 45 mm function

## Technical data

Threefold faceplate, vertical 71 mm centre distance, for a double switch, a socket outlet and a 45x45 function, Niko Toggle alu black brushed.

- Colour: alu black (approximately NCS S 8005 - R50B, RAL 000 20 00)
- Recommended colour central plate: alu black
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of anodised brushed aluminium (alu black).
- Material lower frame: The lower frame is made of dark grey polycarbonate (PC) + acrylic-styrene-acrylate (ASA), black coated.
- Varnish lower frame: The lower frame is enamelled black.
- Frame thickness: The upper frame is 6 mm thick and the lower frame 2 mm.
- Centre-to-centre distance: 71 mm
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 225 x 83 x 13 mm
- Dimensions visible (HxWxD): 225 x 83 mm
- Marking: CE



**niko**

CE

[www.niko.eu](http://www.niko.eu)

**niko**

224-57960 - 28.01.-2025