

Dubbele wandcontactdoos met randaarde en kinderveiligheid, verticaal

Including flush surround plate with integrated central plate. For mounting into a single flush-mounting box.




Dubbele wandcontactdoos met randaarde en kinderveiligheid, verticaal

Including flush surround plate with integrated central plate. For mounting into a single flush-mounting box.



COMPLETE UNIT WITH PLUG-IN TERMINALS, FOR SCREW FIXING



 **100-67865** Pieces: 10

100-67865

4 year
warranty

Double socket outlet with side earthing and shutters, vertical, cream



Double socket outlet with side earthing and shutters, vertical, cream. The sockets are equipped with plug-in terminals for clamping the wires. The socket outlet has side earthing in high quality brass. 2 x 2.5 mm² per connection terminal. The earthing terminal even up to 2 x 2.5 mm² + 2 x 4 mm². When fixing in a flush-mounting box screws should be used. The flush-mounting frame is made of 1 mm-thick metal and is galvanized on all sides. On the horizontal axis, the flush-mounting frame has grooves for mounting into floor sockets with screws. The central plate is made of impact-resistant, dustproof and rigid polycarbonate. The base material is coloured in mass.

- Colour: cream (coloured in mass, approximately RAL 1013)
- Type of earthing: side earthing
- All plastic components are self-extinguishing (comply with a filament test of 650 °C) and are halogen-free.
- Protection degree: The combination of a mechanism, a central plate and a flush surround plate has a protection degree of IP41
- Impact resistance: After mounting, an impact-resistance of IK06 is guaranteed.
- Flush-mounting depth: 26 mm
- Dimensions (HxWxD): 106.8 x 80 x 63 mm
- Marking: CE

