

Onefold faceplate, for single switch functions, Niko Rocker steel white coated

154-56101


4 year warranty

The Niko Rocker onefold faceplate clicks onto a single installed switch function. The faceplate combines with any available Niko Rocker for single switch functions.

It consists of an upper frame, light guide and lower frame that are mechanically interconnected. The upper frame is made of steel. The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated. The upper frame is 2 mm thick and the lower frame 6 mm.

Niko recommends a design combination with the Niko Rocker in the following colour: steel white coated.

- Exclusive materials
- Authentic vintage design
- Belgian design & craftsmanship
- Design matches Niko Pure portfolio
- Proven Niko quality
- Unique illuminated switch design (by adding feedback LED)



Technical data

Onefold faceplate, for single switch functions, Niko Rocker steel white coated.

- Simple faceplate for one switch.
- Colour: enamelled steel white (approximately NCS S 1002 - B50G, RAL 000 90 00)
- Recommended colour central plate: steel white coated
- Frame composition: It consists of an upper frame, light guide and lower frame that are mechanically interconnected.
- Material upper frame: The upper frame is made of steel.
- Material lower frame: The lower frame is made of white polycarbonate (PC) + acrylic-styrene-acrylate (ASA), white coated.
- Varnish upper frame: The upper frame is enamelled white.
- Frame thickness: The upper frame is 2 mm thick and the lower frame 6 mm.
- Lighting element
 - the faceplate is fitted with a light guide
 - the light guide is made of a translucent plastic
 - the light guide transports the light from the optional LED to the lever
 - please note that the faceplate should not be mounted upside down to ensure that the optional LED fits nicely with the light guide
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: The combination of a mechanism, a central plate and a faceplate has a protection degree of IP20D

niko

- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 83 x 12 mm
- Dimensions visible (HxWxD): 83 x 83 x 8 mm
- Certification marks: CEBEC, NF
- Marking: CE

