

Surface-mounting external unit 16 mm with 6 bells

10-156

4 year
warranty

This compact surface-mounting unit in aluminium has a surface-mounting height of only 16 mm. The external unit is equipped with a 5 mm-thick name plate in Plexiglas which is vandal proof. The metal-plated push-button contacts are maintenance-free and durable. This external unit works with 2-wire technology, which means that an existing bell can simply be replaced by this external unit. This external unit has 6 bells.

Technical data

Surface-mounting external unit 16 mm with 6 bells.

- Function:
 - each non-programmed push button can operate the light, light symbol supplied
- Acknowledgement tone when pressing the bell button
- material push buttons: metal with gilded, maintenance-free contacts
- long-life energy-saving name plate lighting
- 5 mm thick, indestructible and vandal proof name place in Plexiglass
- internal memory for the exchange of data between identical external units (EEPROM)
- Mounting method: surface mounting
- Dimensions name field: 19 x 62 mm (HxW)
- Microphone: volume and microphone sensitivity can be adjusted manually
- Wiring technique: 3-wire technology recommended, 2-wire technology possible
- Extra terminal
 - R-terminal to connect an extended function (e.g. door release)
 - door opener time on R-terminal: 3 s (can be adjusted via service unit)
 - activation time of the door relay (for controlling the memory in internal units): 56 s (can be adjusted via service unit).
 - speech connection during activation of the door relay (can be adjusted via service unit)
 - length of conversation: 56 s (can be adjusted via service unit).
- Input current at rest: $I(a) = 0.4 \text{ mA}$, $I(P) = 11 \text{ mA}$ in standby
- Maximum input current: $I(P_{\max}) = 21 \text{ mA}$
- Finishing colour: grey
- Marking: CE

