

# Splashproof single surface-mounting box with one M20 input with cable gland at the top and bottom for one function, white

701-84161

4 year warranty

This surface-mounting box with one M20 input with cable gland at the top and bottom is suitable for one function. The entire unit is splashproof which makes it extremely well-suited for use in damp areas and in ammonia-rich environments. Finishing colour: white

## Technical data

Splashproof single surface-mounting box with one M20 input with cable gland at the top and bottom for one function, white.

- Function: The fixation points are situated 50mm apart on a vertical axis. This size indication is indelibly imprinted on the bottom of each box. The oval screw openings allow for imprecise drilling. By forming a pressure lock, a gasket ensures the protection degree and the double insulation. The box contains two diagonal, knock-out condensation openings.
- Number of mechanisms: 1
- Material surface-mounting box: The surface-mounting box is made of impact-resistant, dust-resistant, halogen-free and self-extinguishing polypropylene (UL94-V2/1.6 mm).
- Protection degree: See protection degree of the mounted function
- Impact resistance: The combination of a Hydro mechanism and a flush- or surface-mounting box has an impact resistance of IK07 with a minimum temperature of -25 °C and a maximum temperature of 55 °C
- Colour: white (mass-dyed, approximately NCS S 0502 - Y50R, RAL 9010)
- Marking: CE

